

(19)

Eur päisch s Patentamt

European Patent Office

Offic européen d s brev ts



(11)

EP 1 213 121 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
12.06.2002 Bulletin 2002/24

(51) Int Cl.7: **B29C 47/02**

(21) Application number: **01308653.3**

(22) Date of filing: **10.10.2001**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Suda, Nobuyuki,**
c/o Bridgestone Corp. Techn. Ctr.
Kodaira-City, Tokyo (JP)

(74) Representative: **Whalley, Kevin**
MARKS & CLERK,
57-60 Lincoln's Inn Fields
London WC2A 3LS (GB)

(30) Priority: **12.10.2000 JP 2000312079**


(71) Applicant: **BRIDGESTONE CORPORATION**
Tokyo 104-0031 (JP)

(54) Process and apparatus for coating belt cord with rubber

(57) In the coating of belt cords with rubber, plural belt cords (C) made of a steel filament are aligned as a cord unit, and a plurality of such cord units are arranged in parallel to each other at a given pitch in the same

plane, and then integrally coated with an uncured rubber (R) through an insulation system immediately after the arrangement of these cord units in line, and apparatus for carrying out the method.

FIG. 1A



Description

[0001] This invention relates to a process and an apparatus for coating a belt cord made of steel filaments for a belt layer as a reinforcement for a tread portion of a pneumatic tire with rubber and attains weight reduction of the belt layer and hence the tire through thinning of such a coating rubber.

[0002] In general, the rubber coating for the conventional belt cord made of twisted steel filaments is carried out by a hot calender system wherein four calender rolls are used to conduct the formation of a rubber sheet and the contact bonding of the rubber sheet to the belt cord, a cord calender system wherein a rubber sheet formed by a sheeting calender of another line is contact-bonded to the belt cord by a coating calender, a semi-hot calender system wherein the formation of a rubber sheet and the contact bonding thereof are carried out on a line by using separate rolls, or the like.

[0003] In anyone of these systems, a relative distance between comb roll or the like arranging plural belt cords in a line and a pair of press rolls contact-bonding the rubber sheet to these cords becomes necessarily large in accordance with the size, arranging state and the like of the press roll and the sheeting roll, so that the mutually arranging state of these cords after the rubber coating is not frequently obtained as is desired and hence the uniformity of strength in the belt layer is damaged and it is apt to easily cause the bending of the belt layer in a direction perpendicular to the extending direction of the cord. And also, the belt cord is easily peeled off from the coating rubber at such a region that the arranging density of the cords becomes high.

[0004] In the conventional calender systems, it is essential to shape the rubber material into the sheet once, so that it is very difficult to extremely thin the thickness of the rubber sheet. As a result, the thickness of the coating rubber to the belt cord becomes necessarily thick and it is obliged to increase the weight of the belt layer and hence the weight of the tire.

[0005] It is, therefore, an object of the invention to solve the aforementioned problems of the conventional technique and to provide a process and an apparatus for coating a belt cord with rubber in which the cord arrangement in a rubber layer after the rubber coating is made regular and the uniformity of strength in the belt layer is enhanced to sufficiently eliminate risks such as bending of the belt layer, peeling of the belt cord and the like and also the weight reduction of the belt layer and the tire can advantageously be realized by decreasing the thickness of the coating rubber to the belt cord, if necessary.

[0006] According to a first aspect of the invention, there is the provision of a process for coating a belt cord with rubber comprising aligning a plurality of belt cords each made of a steel filament as a cord unit, arranging a plurality of such cord units in parallel to each other at a given pitch in the same plane, and integrally coating

all cords with an uncured rubber at a given outer profile shape through an insulation system under a movement of the cord in its axial direction immediately after the arrangement of these cord units in line.

[0007] According to this process, the uncured rubber is directly coated onto all of the belt cords through the insulation system without shaping into a rubber sheet immediately after the arrangement of these cords in line, so that these cords can be subjected to rubber coating prior to the occurrence of disorder in the cord arrangement in line and hence the disorder of the cords in the coating rubber layer can sufficiently be prevented. And also, the thickness of the coating rubber can simply and easily be made to an expected value, so that the gauge of the coating rubber including the belt cord can be reduced to about 2/3 of the gauge in the conventional technique.

[0008] Since the steel filament is used as the belt cord, the twisting work for the belt cord becomes useless and hence the working efficiency for the formation of the cord is largely improved. And also, the extensible deformation of the belt cord resulted from the twisting can effectively be prevented. Furthermore, the cord diameter is made thinner than that of the twisted cord, so that the gauge of the coating rubber including the belt cord can be more reduced to effectively attain the weight reduction of the belt layer.

[0009] In addition, the cord unit comprised of plural steel filaments is coated with rubber, so that the same properties as in the single twisted cord can be given to the cord unit. Further, individual cords in the cord unit are contacted with each other over full length thereof, and these cord units are extended in parallel to each other at a given pitch in the same plane, so that the rigidity of the belt layer can be enhanced to effectively improve the performances and durable life of the tire.

[0010] Moreover, the plural cord units subjected to rubber coating by the process according to the invention are successively cut at a given inclination angle corresponding to a required extending angle of the belt cord every a length corresponding to a required belt width, and then side edges of such band-shaped cuts are regularly joined to each other under a constant outer profile form for the formation of the belt layer.

[0011] From a viewpoint of the weight reduction of the belt layer, it is possible to reduce the weight as the diameter of the belt cord becomes thinner, but when the diameter is too thin, the end count of the cord increases for holding the belt strength and hence the distance between the cords becomes narrower and the resistance to peeling at the end of the belt lowers. On the other hand, when the diameter is too thick, strain produced between the belt cord and the coating rubber increases in the bending deformation of the belt layer and hence the cord is easily bent at a large deformation. For this end, a filament diameter of the belt cord is preferable to be within a range of 0.18-0.35 mm.

[0012] Further, it is favorable that a gauge of the un-

cured coating rubber including the belt cord is within a range of 0.5-1.2 mm in order to effectively attain the further weight reduction of the belt layer.

[0013] According to a second aspect of the invention, there is the provision of an apparatus for coating belt cords with rubber comprising an insulator head arranged on a top of a cylinder provided with a screw in an extruder for an uncured rubber, an inserter arranged in the insulator head for guiding plural belt cords so as to pass them at a required relative posture, and a die for coating the belt cords after the pass through the inserter with an uncured rubber supplied from the cylinder at a required outer profile shape.

[0014] The apparatus according to the invention is suitable for carrying out the above coating process. In this apparatus, a rubber material fed into the extruder is warmed in the cylinder and extruded through the die at the insulator head in the required outer profile shape, while the plural belt cords arranged at the relative posture in the inserter in line are passed through the die, whereby each of these cords immediately after the pass through the inserter is coated with the warmed rubber material in the die or uncured rubber. In this way, the rubber coating for each of these cords arranged in line by the inserter is ensured, and also the gauge of the coating rubber can be thinned as it is expected without fearing the peeling of the coating rubber from the cord or the like.

[0015] In a preferable embodiment of the second aspect, a pressure sensor for the uncured rubber is arranged in the insulator head. In this case, results detected by the sensor are fed back to a rotating speed of the screw in the cylinder to maintain the pressure of the uncured rubber in the die at a constant value, whereby the gauge of the uncured coating rubber extruded through the die or the like can be held constant to more stability the quality of the rubber coated product.

[0016] In another preferable embodiment of the second aspect, the inserter is provided with plural holes each passing a plurality of belt cords as a cord unit and specifying the relative posture of these cords every the cord unit.

[0017] In this case, the cords can be subjected to rubber coating while holding the relative posture of the cords as a cord unit at a constant state, and also the relative posture can be maintained in a longitudinal direction of the cord and between the cord units, whereby the quality of the rubber coated product can be more stabilized.

[0018] On the other hand, if the conventional comb roll having plural annular grooves or recesses is used instead of the inserter and plural belt cords as a cord unit are guided by each of the grooves or recesses, it is substantially impossible to maintain the relative posture of the cords at a constant state in the longitudinal direction of the cord and between the cord units because the position of each cord can not effectively be controlled only by the groove or the like, and hence there is caused

the scattering in the quality and the tire performances.
[0019] The invention will be described with reference to the accompanying drawings, wherein:

FIG. 1A is a diagrammatically perspective view of an embodiment of the apparatus according to the invention;

FIG. 1B is a diagrammatically section view taken along a line I-I of FIG. 1A;

FIG. 2A is a diagrammatically partial section view illustrating an embodiment of the hole in the inserter according to the invention taken along a line II-II of FIG. 1B;

FIG. 2B is a schematic view of another embodiment of the hole in the inserter according to the invention; FIG. 3 is a partial perspective view illustrating a state of passing belt cords through holes in the inserter according to the invention; and

FIG. 4A is a partial schematic view of an embodiment of the belt layer according to the invention; and FIG. 4B is a diagrammatically partial section view taken along a line IV-IV of FIG. 4A.

[0020] In FIGS. 1A and 1B is shown an embodiment of the apparatus for rubber coating according to the invention. In this apparatus, an extruder 1 comprises a hopper 2 allowing to feed slitting rubber or other rubber material and a cylinder 3 provided therein with a screw. The rubber material is warmed under an action of the screw and transferred into a top of the cylinder 3.

[0021] To the top of the cylinder 3 is attached an insulator head 4. As shown in FIG. 1B, an inserter 5 for guiding plural belt cords C so as to pass at a required relative posture is arranged in the insulator head 4, and also a die 6 for coating the belt cords C after the pass through the inserter 5 with an uncured rubber R fed from the cylinder 3 at a required outer profile shape is arranged adjacent to the inserter 5 ahead thereof in the head 4.

[0022] The inserter 5 is incorporated into the head 4 while holding with an inserter holder 7, while the die 6 is comprised of an upper die portion 6a and a lower die portion 6b. A space zone between these portions 6a and 6b, particularly an outlet zone thereof specifies an outer profile shape including a gauge, width and the like of the uncured rubber R and hence the coating rubber including the cords. Moreover, the die 6 and the inserter holder 7 are at a state of restraining to each other, so that they do not relatively move in up-down direction and front-back direction.

[0023] As shown in FIG. 2A, the inserter 5 is provided with a plurality of holes 5a, oval-shaped holes 5a in the illustrated embodiment each passing plural belt cords each made of a steel filament, three belt cords C1, C2, C3 in the illustrated embodiment as a cord unit and specifying a relative posture of these cords, wherein these holes 5a are arranged at a given interval in line and a peripheral wall of each hole 5a acts to effectively

restrain the change of the relative posture of these cords C1, C2, C3. As the profile shape of the hole 5a, a necked part may be formed between the cords as shown in FIG. 2B, whereby the posture of the cord C1, C2, C3 can be specified more effectively.

[0024] In FIG. 3 is perspectively shown a state of passing the cords through the holes 5a formed in the inserter 5, wherein plural cord units, each of which units being comprised of three cords C arranged at the required relative posture in line by the peripheral wall of the hole 5a, are continuously drawn out from the holes 5a so as to extend in parallel to each other at a given pitch in the same plane.

[0025] On the other hand, the warmed uncured rubber R is supplied through the space zone between the die 6 and the inserter 5, and the individual cords immediately after the pass through the holes 5a are closely coated around their peripheries and integrally united with such an uncured rubber R, which is extruded from an outlet port of the die 6 at the required outer profile shape as shown in FIG. 1B.

[0026] Thus, the individual cords C arranged after the pass through the inserter 5 are immediately restrained by the uncured coating rubber R, whereby the disorder of these cords C can sufficiently be prevented. And also, the gauge of the coating rubber to the cord C can properly be adjusted by specifying the extrusion size to the warmed uncured rubber R through the die 6, if necessary, so that the gauge including the cord C can be made sufficiently thinner than that of the conventional technique.

[0027] In FIG. 1A, numeral 8 is a pressure sensor attached to the insulator head 4 for measuring a pressure of the warmed uncured rubber R supplied to the space zone between the inserter 5 and the die 6. The results measured by the pressure sensor 8 can be fed back to, for example, a driving means for the screw in the cylinder 3 to control the rotating speed of the screw, whereby the pressure of the uncured rubber R can be adjusted to a given range to sufficiently enhance various dimensions of a band-shaped body extruded through the die 6 and comprised of the coating uncured rubber R and the belt cords C.

[0028] As shown in FIG. 4A, the band-shaped body formed by the above apparatus and comprised of the coating uncured rubber R and the belt cords C (e.g. steel filaments having a diameter of 0.2 mm) is successively cut at an inclination angle corresponding to a required extending angle α of the belt cord C every length corresponding to a required belt width BW, and then the band-shaped cuts CC are joined at their side edges to each other as shown in FIG. 4B, whereby a belt layer B can be formed at a given value of a gauge t of the coating rubber including the cord C, for example, a gauge t of 0.87 mm.

[0029] As mentioned above, according to the invention, the belt cords each comprised of a steel filament are integrally coated with the uncured rubber through

the insulation system using the die immediately after these cords are arranged in line, whereby the arranging posture of these cords after the coating can be made as it is expected, and also the gauge of the coating rubber including the cord can be decreased, if necessary, to realize the weight reduction of the belt layer and hence the tire.

10 Claims

1. A process for coating a belt cord with rubber comprising aligning a plurality of belt cords (C) each made of a steel filament as a cord unit, arranging a plurality of said cord units in parallel to each other at a given pitch in the same plane, and integrally coating all cords with an uncured rubber (R) at a given outer profile shape through an insulation system under movement of the cord in its axial direction immediately after the arrangement of said cord units in line.
2. A process as claimed in claim 1, **characterized in that** the filament diameter of the belt cord is within a range of 0.18-0.35 mm.
3. A process as claimed in claim 1 or 2, **characterized in that** the gauge of the uncured coating rubber including the belt cord is within a range of 0.5-1.2 mm.
4. Apparatus for coating belt cords with rubber comprising an insulator head (4) arranged at an end of a cylinder (3) provided with a screw in an extruder (1) for an uncured rubber, an inserter (5) arranged in the insulator head for guiding plural belt cords (C) so as to pass them at a required relative posture, and a die (6) for coating the belt cords after the pass through the inserter with an uncured rubber (R) supplied from the cylinder at a required outer profile shape.
5. Apparatus as claimed in claim 4, **characterized in that** a pressure sensor (8) for the uncured rubber (R) is arranged in or attached to the insulator head (4).
6. Apparatus as claimed in claims 4 or 5, **characterized in that** the inserter (5) is provided with plural holes (5a) each passing a plurality of belt cords (C1,C2,C3) as a cord unit and specifying the relative posture of said cords every cord unit.

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A





FIG. 4B





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 8653

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 4 126 720 A (EDWARDS GEORGE R) 21 November 1978 (1978-11-21) * abstract * * figure 1 * * column 5, line 6 - line 22 * * column 5, line 47 - line 56 *	1-4,6	B29C47/02
X	EP 0 478 258 A (SUMITOMO RUBBER IND) 1 April 1992 (1992-04-01) * abstract * * column 3, line 5 - line 32 * * column 3, line 43 - column 4, line 35 * * claims; figures *	1-5	
X	US 5 374 324 A (BLASINGAME BENJAMIN C ET AL) 20 December 1994 (1994-12-20) * abstract * * figures 1-5 * * column 2, line 56 - column 3, line 27 *	1,4,6	
A		2,3,5	
X	EP 0 619 170 A (GOODYEAR TIRE & RUBBER) 12 October 1994 (1994-10-12) * column 3, line 56 - column 4, line 4; figure 4 *	1,4-6	TECHNICAL FIELDS SEARCHED (Int.Cl.7) B29C B29H
X	US 4 300 878 A (IBLE DONALD G) 17 November 1981 (1981-11-17) * the whole document *	1,4,6	
A		2,3,5	
A	DE 195 45 079 A (PHOENIX AG) 13 June 1996 (1996-06-13) * column 2, line 49 - column 3, line 13 * * claims 19-24; figures *	1-3	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 23 January 2002	Examiner Jensen, K
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application I : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 8653

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-01-2002

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 4126720	A	21-11-1978	AU	2534477 A	23-11-1978
			DE	2723698 A1	22-12-1977
			FR	2351778 A1	16-12-1977
			JP	53004081 A	14-01-1978
			LU	77392 A1	26-09-1977
EP 0478258	A	01-04-1992	JP	1998407 C	08-12-1995
			JP	4131218 A	01-05-1992
			JP	7020654 B	08-03-1995
			DE	69120010 D1	11-07-1996
			DE	69120010 T2	24-10-1996
			EP	0478258 A2	01-04-1992
			US	5171502 A	15-12-1992
US 5374324	A	20-12-1994	CA	2049587 A1	01-03-1992
			MX	9100826 A1	01-04-1992
EP 0619170	A	12-10-1994	AU	671709 B2	05-09-1996
			AU	5787294 A	22-09-1994
			BR	9401206 A	08-11-1994
			CA	2097642 A1	20-09-1994
			DE	69418526 D1	24-06-1999
			DE	69418526 T2	11-11-1999
			EP	0619170 A2	12-10-1994
			ES	2132270 T3	16-08-1999
			JP	6315964 A	15-11-1994
US 4300878	A	17-11-1981	AU	539955 B2	25-10-1984
			AU	7424981 A	04-03-1982
			BR	8105454 A	11-05-1982
			DE	3173193 D1	23-01-1986
			EP	0046688 A2	03-03-1982
			ES	268629 Y	01-02-1984
			JP	1361189 C	30-01-1987
			JP	57074141 A	10-05-1982
			JP	61028498 B	30-06-1986
			KE	3640 A	20-06-1986
			MX	158394 A	30-01-1989
			NO	812815 A	01-03-1982
			NZ	198168 A	19-10-1984
			PH	18360 A	13-06-1985
			PT	73570 A B	01-09-1931
			ZA	8105578 A	25-08-1982
DE 19545079	A	13-06-1996	DE	19545079 A1	13-06-1996